

GENERAL LIGHTING - RECESSED DOWNLIGHT

C-GENERAL-REC DL1-R-ADJUSTABLE

(available only when ordered with a Cooledge Specialty Illumination Solution)



APPLICATION

- Adjustable recessed downlight - round
- 500mA DC LED power supply
- For indoor use only

PHOTOMETRIC

- Light Source: LED 9W (10W @ 500mA)
- CRI: >90

MECHANICAL

- Dimensions: Height = 2-3/16" (56mm); Diameter = 3" (77mm)
- Adjustable Range: Angle = 0°- 30°; Rotational = 360°
- IP Rating: IP20
- Weight: 0.4lbs (0.18kg)

ELECTRICAL

- 500mA DC (contact Cooledge for ordering information)

MOUNTING

- Cut Out Size: Diameter = 2-3/4" (70mm)
- Recessed Depth: 2-3/8" (60mm)
- Mounting Surface Thickness: min. 3/16" (5mm)

FINISH COLOR

Add your selection using the following codes:


- B – Black
- W – White

ACCESSORIES



Required:

- Housing (contact Cooledge for order info)

HOUSING



Beam angles available: 37° (FL)



● Indicative opening

IC/NIC AT S 500mA-DC 10,5W 0-10V
dim 120-277V

Beam Angle	3000K			3500K		
	Source Lumens	Delivered Lumens	Order Code	Source Lumens	Delivered Lumens	Order Code
37° (FL)	1076	749	C-6 19354 9330	1102	767	C-6 19354 9530