

GENERAL LIGHTING - RECESSED DOWNLIGHT

C-GENERAL-REC DL2-R

(available only when ordered with a Cooledge Specialty Illumination Solution)



APPLICATION

- Recessed downlight - round
- 500mA DC LED power supply
- For indoor use only

PHOTOMETRIC

- Light Source: LED 9W (with PSU = 10W)
- CRI: >90

MECHANICAL

- Dimensions: Height = 3-1/4" (82mm); LxW = 3-3/16" (81mm)
- IP Rating: IP20
- Weight: 0.4lbs (0.18kg)

ELECTRICAL

- Power Supply: 500mA DC (included with rough-in/remodel)

MOUNTING

- Cut Out Size: Diameter = 3" (76mm)
- Recessed Depth: 3-15/16" (100mm)
- Mounting Surface Thickness: min. 3/16" (5mm)

FINISH COLOR


Add your selection using the following codes:

- B-B – Black
- W-W – White


ACCESSORIES

Required:

- Housing, Plasterframe, or Remodel (contact Cooledge for order info)



Beam angles available: 18° (SP), 25° (FL) shown, 37° (FL)



Beam Angle	3000K			3500K		
	Source Lumens	Delivered Lumens	Order Code	Source Lumens	Delivered Lumens	Order Code
18° (SP)	1076	817	C-6 25213 9310	1102	837	C-6 25213 9510
25° (FL)	1076	813	C-6 25213 9320	1102	834	C-6 25213 9520
37° (FL)	1076	873	C-6 25213 9330	1102	894	C-6 25213 9530

HOUSING	PLASTERFRAME	REMODEL
<p>S-SMALL: A:12"-23/32 x B:11"-1/6 x C:4"-13/16 A:323mm x B:281mm x C:122mm</p>	<p>S-SMALL: A:15"-7/16 x B:12"-1/4 x C:5" A:390mm x B:311mm x C:127mm</p>	<p>A:10"-13/16 x B:2"-1/2 x C:2"-19/32 A:275mm x B:64mm x C:66mm</p>

SPECIFICATION SHEET

GENERAL LIGHTING - RECESSED DOWNLIGHT

C-GENERAL-REC DL2-R-ADJUSTABLE

(available only when ordered with a Cooledge Specialty Illumination Solution)

APPLICATION

- Adjustable recessed downlight
- 500mA DC LED power supply
- For indoor use only

PHOTOMETRIC

- Light Source: LED 9W (with PSU = 10W)
- CRI: >90

MECHANICAL

- Dimensions: Height = 3-1/2" (88mm); Diameter = 3-3/16" (81mm)
- Adjustable Range: Angle = 0°- 20°; Rotational = 355°
- IP Rating: IP20
- Weight: 0.4lbs (0.18kg)

ELECTRICAL

- Power Supply: 500mA DC (included with rough-in/remodel)

MOUNTING

- Cut Out Size: Diameter = 3" (76mm)
- Recessed Depth: 3-9/16" (90mm)
- Mounting Surface Thickness: min. 3/16" (5mm)

FINISH COLOR


Add your selection using the following codes:

- B-B – Black
- W-W – White


ACCESSORIES

Required:

- Housing, Plasterframe, or Remodel (contact Cooledge for order info)



Beam angles available: 18° (SP), 25° (FL) shown, 37° (FL)



Beam Angle	3000K			3500K		
	Source Lumens	Delivered Lumens	Order Code	Source Lumens	Delivered Lumens	Order Code
18° (SP)	1076	835	C-6 25214 9310	1102	855	C-6 25214 9510
25° (FL)	1076	872	C-6 25214 9320	1102	894	C-6 25214 9520
37° (FL)	1076	909	C-6 25214 9330	1102	931	C-6 25214 9530

HOUSING	PLASTERFRAME	REMODEL
<p>S-SMALL: A:12"-23/32 x B:11"-1/6 x C:4"-13/16 A:323mm x B:281mm x C:122mm</p> <p>IC AT</p>	<p>S-SMALL: A:15"-7/16 x B:12"-1/4 x C:5" A:390mm x B:311mm x C:127mm</p> <p>NIC</p>	<p>A:10"-13/16 x B: 2"-1/2 x C: 2"-19/32 A:275mm x B: 64mm x C: 66mm</p> <p>NIC</p>

SPECIFICATION SHEET

GENERAL LIGHTING - RECESSED DOWNLIGHT

C-GENERAL-REC DL2-S

(available only when ordered with a Cooledge Specialty Illumination Solution)

APPLICATION

- Recessed downlight - square
- 500mA DC LED power supply
- For indoor use only

PHOTOMETRIC

- Light Source: LED 9W (with PSU = 10W)
- CRI: >90

MECHANICAL

- Dimensions: Height = 3-1/4" (82mm); LxW = 3-3/16" (81mm)
- IP Rating: IP20
- Weight: 0.4lbs (0.18kg)

ELECTRICAL

- Power Supply: 500mA DC (included with rough-in/remodel)

MOUNTING

- Cut Out Size: 3" x 3" (76mm x 76mm)
- Recessed Depth: 3-15/16" (100mm)
- Mounting Surface Thickness: min. 3/16" (5mm)

FINISH COLOR



Add your selection using the following codes:

- B-B – Black
- W-W – White

ACCESSORIES

Required:

- Housing, Plasterframe, or Remodel (contact Cooledge for order info)



Beam Angle	3000K			3500K		
	Source Lumens	Delivered Lumens	Order Code	Source Lumens	Delivered Lumens	Order Code
18° (SP)	1076	799	C-6 25216 9310	1102	819	C-6 25216 9510
25° (FL)	1076	826	C-6 25216 9320	1102	846	C-6 25216 9520
37° (FL)	1076	835	C-6 25216 9330	1102	855	C-6 25216 9530

HOUSING	PLASTERFRAME	REMODEL
S-SMALL: A:12"-23/32 x B:11"-1/6 x C:4"-13/16 A:323mm x B:281mm x C:122mm	S-SMALL: A:15"-7/16 x B:12"-1/4 x C:5" A:390mm x B:311mm x C:127mm	A: 10"-13/16 x B: 2"-1/2 x C: 2"-19/32 A:275mm x B:64mm x C:66mm