

COOLEEDGE™

COOLEEDGE LIGHT QUALITY METRICS: TILE INTERIOR - 2700K

NOTES ABOUT LIGHT QUALITY METRICS DATA:

- Values shown are TYPICAL – actual performance of individual units may vary
- The data presented has been generated in accordance with LM-79-08
- A complete summary of LM-79-08 data is provided for 600 lm/sqft (6450 lm/m²) TILE models only; however, spectral and color rendering data is applicable to TILE models of the same CCT at lower lumen output levels (150/1600 & 300/3225), including:
 - Spectral Power Distribution (SPD)
 - Nominal CCT
 - Chromaticity
 - R_f and R_g (TM-30-15)
 - CRI (R_a) and R-values
 - D_{uv}

SELECTED DEFINITIONS

- **Candlepower:** As presented in this document it is the same as “candela” the SI unit of measurement for light intensity.
- **CRI (R_a):** The general Color Rendering Index based on 8 CIE reference pastel color samples.
- **D_{uv} :** The American National Standards Institute (ANSI) references D_{uv} , a metric based on the CIE 1976 color space that quantifies the distance between the chromaticity of a given light source and a blackbody radiator of equal CCT. A negative D_{uv} indicates that the source is “below” the Planckian locus (blackbody curve), potentially having a red/blue tint, whereas a positive D_{uv} indicates that the source is “above” the curve, potentially exhibiting a green tint.
- **Nominal CCT Quadrangles:** ANSI has defined acceptable chromaticity quadrangles for LED binning in relation to the blackbody curve within CIE color space. The data presented shows the typical chromaticity coordinate within the relevant quadrangle.
- **R-value (R_i):** The R-value is a mathematical calculation measuring how similar a light source renders a particular color compared to a reference blackbody source of the same CCT. R-values are not absolute and therefore cannot be used as a specific measurement of color rendering. For example, a 2700K source may have a lower R9 value than a 5700K source, however, in absolute terms the 2700K source will render saturated red much better than the 5700K source because of the relative abundance of red in the spectral power distribution (SPD) for the 2700K source in comparison.
- **R1-R15:** The data presented include the special CRI set of CIE 14 samples and the Japanese Industrial Standard (JIS) for R15.
- **R_f :** The IESNA TM-30-15 technical memorandum for measuring color rendering defines a “fidelity” index, R_f , that is similar to CRI and quantifies the average difference in appearance between the test source and a reference source based on 99 reference colors.
- **R_g :** The IESNA TM-30-15 technical memorandum for measuring color rendering defines a “gamut” index, R_g , that quantifies the average difference in color saturation between the test source and a reference source based on 99 reference colors.

COOLEGE LIGHT QUALITY METRICS: TILE INTERIOR - 2700K

LIGHTING PROPERTIES: TYPICAL PERFORMANCE


TEST CONDITIONS

Temp (°C)	DC Voltage (V)	Current (A)	Power (W)
22.4	58.0	0.1012	5.87

COLOR RENDERING INDEX DETAILS

Reference	Value
R1	92
R2	98
R3	97
R4	90
R5	92
R6	97
R7	89
R8	78
R9	55
R10	93
R11	90
R12	81
R13	94
R14	100
R15	88

NOMINAL CCT QUADRANGLES



CHROMATICITY COORDINATES

Chromaticity (x)	.04592
Chromaticity (y)	0.4071
Chromaticity (u)	0.2637
Chromaticity (v)	0.3506
Chromaticity (u)	0.2637
Chromaticity (v)	0.5259
Duv	-0.0012


SUMMARY OF RESULTS

Total Lumen Output	605 Lumens
Luminaire Efficacy	103 lm/W
Maximum Candela	199 Candela
CCT	2682 K
CRI (Ra)	91
Duv	-0.0012
TM-30 R _f	88
TM-30 R _g	97

INTENSITY (CANDLEPOWER) SUMMARY

Angle	Mean CP	Lumens
0	199.2	
5	198.4	605
10	196.2	
15	192.5	586
20	187.3	
25	180.6	540
30	172.4	
35	162.7	464
40	151.4	
45	138.8	365
50	124.9	
55	109.8	258
60	93.7	
65	77.0	157
70	60.1	
75	43.6	73
80	28.7	
85	16.7	19
90	8.3	

SPECTRAL POWER DISTRIBUTION (SPD)



Testing was performed in accordance with LM-79-08.

POLAR GRAPH

