

TRACK MOUNTED - SPOT/FLOOD

C-TRACK-SF H2-SPOT

(available only when ordered with a Cooledge Specialty Illumination Solution)



APPLICATION

- Track mounted - intended for use with magnetic profiles
- 48VDC remote LED power supply is required (not included)
- For indoor use only

PHOTOMETRIC

- Light Source: LED 5.7W (with PSU = 7W)
- CRI: >90

MECHANICAL

- Dimensions: Height = 4-9/16" (116mm); Diameter = 2" (50mm)
- Adjustable Range: Angle = 0°- 90°; Rotational = 355°
- IP Rating: IP20
- Weight: 0.9lbs (0.41kg)
- Compatible with M20 & M26H track size

ELECTRICAL

- Power Supply: Remote 48VDC (not included)
- Input Voltage: 120VAC (60Hz)

Dimming:

- DIM5 = DALI
- MDL = DALI / 0-10V / Push Button via 48V modulator

FINISH COLOR

Add your selection using the following codes:

- **GC** - Gold
- **BBR** - Black Bronze


ACCESSORIES

Required:


- TUBE

Optional:

- HONEYCOMB
- SOFTENING LENS



Beam angles available: 8° (SP)



Beam Angle	3000K			3500K		
	Source Lumens	Delivered Lumens	Order Code	Source Lumens	Delivered Lumens	Order Code
8° (SP)	519	397	C-6 23366 9310 (MDL) C-6 23363 9315 (DIM5)	519	397	C-6 23366 9510 (MDL) C-6 23363 9515 (DIM5)

TRACK MOUNTED - SPOT/FLOOD

C-TRACK-SF H2-FLOOD

(available only when ordered with a Cooleedge Specialty Illumination Solution)

APPLICATION

- Track mounted - intended for use with magnetic profiles
- 48VDC remote LED power supply is required (not included)
- For indoor use only

PHOTOMETRIC

- Light Source: LED 10.4W (with PSU = 12W)
- CRI: >90

MECHANICAL

- Dimensions: Height = 5-15/16" (150mm); Diameter = 2" (50mm)
- Adjustable Range: Angle = 0°- 90°; Rotational = 355°
- IP Rating: IP20
- Weight: 1.1lbs (0.50kg)
- Compatible with M20 & M26H track size

ELECTRICAL

- Power Supply: Remote 48VDC (not included)
- Input Voltage: 120VAC (60Hz)

Dimming:

- DIM5 = DALI

FINISH COLOR

Add your selection using the following codes:

- **GC** - Gold
- **BBR** - Black Bronze


ACCESSORIES

Required:


- TUBE

Optional:

- HONEYCOMB
- SOFTENING LENS



Beam angles available: 33° (FL)



Beam Angle	3000K			3500K		
	Source Lumens	Delivered Lumens	Order Code	Source Lumens	Delivered Lumens	Order Code
33° (FL)	1128	566	C-6 23364 9325 (DIM5)	1163	584	C-6 23364 9525 (DIM5)